



**Art. No.: 31285**  
**Ambus J-Carrier**  
**holder for cylindrical fuses Class J, 30 A**  
**2-pole**

**Product Group : 16**  
**Subgroup : 03**

**Standards :**  
UL 512  
CSA C22.2 No. 39

**Approvals :**  
GOST, CSA, UL (approved for feeder circuits to UL 508A up to 600 V)

Type No.: AJC 30  
Duty Tariff No.: 8536 30 30

UL File Number: E230163, Category: IZLT, [www.ul.com](http://www.ul.com)  
CSA File Number: 110285, Class Number: 6225-01, <http://directories.csa-international.org>

**Electrical Data :**  
30 A, 600 V (60 Hz)  
rated insulation voltage : 800 V  
for fuse links Class J to UL 248-8

**Mechanical Data :**  
Width x Height x Depth (mm): 72 x 115 x 69  
Weight (kg/100): 32,2  
Fastening method:  
clip-on mounting

**Connections :**

box terminal :

2,5 - 50 mm<sup>2</sup> / AWG 14 - AWG 1

flexible cables, directly or with wire-end ferrule

Md 3,5 - 4,0 Nm / 31 - 35 lb.in.

(flexible cables of maximum cross-section may not fit when using wire-end ferrule)

**Versions :**

1P : part no. 31284

3P : part no. 31287

**Pack Size : 3**

**Catalog 2006 :**

Page: 6/12

**Accessories to Article 31285 :**



31939 label for AES  
100x 10 pcs.