



Art. No.: 31920
Ambus J-Carrier
holder for cylindrical fuses Class J, 60 A
1-pole
New Article

Product Group : 16
Subgroup : 06

Standards :
UL 512
CSA C22.2 No. 39

Approvals :
GOST, CSA, UL (approved for feeder circuits to UL 508A up to 600 V)

Type No.: AJC 60
Duty Tariff No.: 8536 30 30

UL File Number: E230163, Category: IZLT, www.ul.com
CSA File Number: 110285, Class Number: 6225-01, <http://directories.csa-international.org>

Electrical Data :
60 A, 600 V (60 Hz)
rated insulation voltage : 800 V
for fuse links Class J to UL 248-8

Mechanical Data :
Width x Height x Depth (mm): 40 x 118 x 82
Weight (kg/100): 18,2
Fastening method:
clip-on mounting

Connections :

box terminal :

6 - 50 mm² / AWG 10 - AWG 1

flexible cables, directly or with wire-end ferrule

Md 3,5 - 4,0 Nm / 31 - 35 lb.in.

(flexible cables of maximum cross-section may not fit when using wire-end ferrule)

Versions :

2P : part no. 31921


3P : part no. 31922

Pack Size : 6


Catalog 2006 :

Page: 6/12

Accessories to Article 31920 :




31360 fuse link 35 A, time delay
600 V AC, 500 V DC



31361 fuse link 40 A, time delay
600 V AC, 500 V DC




31362 fuse link 45 A, time delay
600 V AC, 500 V DC



31363 fuse link 50 A, time delay
600 V AC, 500 V DC

Accessories to Article 31920 :

<p>kein Produktbild verfügbar</p> <p>no picture available</p>	<p>31364 fuse link 60 A, time delay 600 V AC, 500 V DC</p>
<p>kein Produktbild verfügbar</p> <p>no picture available</p>	<p>31511 fuse link 35 A, fast acting 600 V AC, 300 V DC</p>
<p>kein Produktbild verfügbar</p> <p>no picture available</p>	<p>31512 fuse link 40 A, fast acting 600 V AC, 300 V DC</p>
<p>kein Produktbild verfügbar</p> <p>no picture available</p>	<p>31513 fuse link 45 A, fast acting 600 V AC, 300 V DC</p>
<p>kein Produktbild verfügbar</p> <p>no picture available</p>	<p>31514 fuse link 50 A, fast acting 600 V AC, 300 V DC</p>
<p>kein Produktbild verfügbar</p> <p>no picture available</p>	<p>31515 fuse link 60 A, fast acting 600 V AC, 300 V DC</p>
	<p>31939 label for AES 100x 10 pcs.</p>

Wöhner reserves the right to make modifications to its components, as the result of developments and technical advances.