



Art. No.: 33306
Fuse base Class J 61-100A
panel mounting

Product Group : 16
Subgroup : 09

Standards :
UL 512
CSA C22.2 No. 39

Approvals :
GOST, CSA, UL (approved for feeder circuits to UL 508A up to 600 V)

Type No.: JC100
Duty Tariff No.: 8536 30 30

UL File Number: E230163, Category: IZLT, www.ul.com
CSA File Number: 110285, Class Number: 3211-37, <http://directories.csa-international.org>

Electrical Data :
3-pole, 600 V a.c.
rated short-circuit current 200 kA
for fuse links Class J to UL 248-8

Mechanical Data :
Width x Height x Depth (mm): 184 x 215 x 83
Weight (kg/100): 217,6
screw mounting to mounting plate,
terminal 6-70 mm², re, rm, f, f + AE; AWG 10-2/0, 14-16 Nm / 125-142 lb.in.

Remarks :
cover cap included

Pack Size : 1

Catalog 2006 :
Page: 6/12

Accessories to Article 33306 :



03214 fuse link 70 A, fast acting
600 V AC, 300 V DC



03215 fuse link 80 A, fast acting
600 V AC, 300 V DC



03216 fuse link 90 A, fast acting
600 V AC, 300 V DC



03217 fuse link 100 A, fast acting
600 V AC, 300 V DC



03228 fuse link 70 A, time delay
600 V AC, 500 V DC



03229 fuse link 80 A, time delay
600 V AC, 500 V DC

Wöhner reserves the right to make modifications to its components, as the result of developments and technical advances.

Accessories to Article 33306 :



03230 fuse link 90 A, time delay
600 V AC, 500 V DC



03231 fuse link 100 A, time delay
600 V AC, 500 V DC